

Combining Crowd Sensing and Social Data Mining with Agent-based Simulation using Mobile Agents towards Augmented Virtuality

Stefan Bosse¹, Uwe Engel²

¹University of Koblenz-Landau, Fac. Computer Science, Koblenz, ²University of Bremen, Dept. Social Science, Bremen

Abstract: Augmented reality is well known for extending the real world by adding computer-generated perceptual information and overlaid sensory information. In contrast, simulation worlds are commonly closed and rely on artificial social behaviour and synthetic sensory information generated by the simulator program or using data collected off-line by surveys. Agent-based modelling used for investigation and evaluation of social interaction and networking relies on parameterisable models. Finding accurate and representative parameter settings can be a challenge. In this work, a new simulation paradigm is introduced, providing augmented virtuality by coupling crowd sensing and social data mining with simulation worlds by using mobile agents in a unified way. A simple social network analysis case-study based on the Sakoda social interaction model and mobile crowd sensing demonstrate the capabilities of the new hybrid simulation method.

I. Introduction

The key concept of this work is the consideration of humans as sensors. This concept is highly interdisciplinary and is a merit of social and computer science if the human sensor data will be coupled with social interaction and networking models. Social interaction has a high impact on the control and evolution of complex social systems, which should be addressed in this work.

Agent-based methods are established for modelling and studying of complex dynamic systems and for implementing distributed intelligent systems, e.g., in traffic and transportation control (see [1] and [2]). Therefore, agent-based methods can be divided into the following main classes and paradigm [3]:

1. Agent-based Modelling (ABM) - Modelling of complex dynamic systems by using the agent behaviour and interaction model ⇒ **Physical agents**
2. Agent-based Computing (ABC) - Distributed and parallel computing using mobile agents related to mobile software processes ⇒ **Computational agents**

- 3. Agent-based Simulation (ABS) - Simulation of agents or using agents for simulation
- 4. Agent-based Computation, Modelling, and Simulation (ABX) - **Combining physical and computational agents**

The fourth paradigm is the novelty introduced in this work with application to social mobility and network simulation.




Figure 1: (Left) Traditional ABMS with separate field studies (Right) New ABX combining modelling, simulation, and field studies via crowd sensing

ABS is suitable for studying complex social systems with respect to interaction between individual entities, manipulation of the world, spatial movement, and emergence effects of groups of entities. The main advantage is the bottom-up modelling approach composing large-scale complex systems by simple entity models. The main disadvantage of ABM is the (over-) simplified entity behaviour and simplification of the world the entities acting in. Commonly, simulation bases on synthetic data or data retrieved by field studies. Many simulations and models lacking of diversity that are existing in real world. Commonly, sensor and model data (parameters) used in simulations (virtual world) is retrieved from experiments or field studies (real world), shown in Fig. 1. But there is neither a feedback from the virtual to the real world nor an interaction of the real world with the virtual world. ABC is mainly used to implement adaptive and self-organising distributed computing. In this work, a different simulation approach combining ABM, ABC, and ABS methodologies (ABX), is used deploying the widely used programming language JavaScript. JavaScript is an easy to learn programming language that was used originally in WEB development, but is increasingly

used as a generic programming language and for ABS [4].

Crowd sensing (CWS) can be considered as part of field studies [5], either performed in a participatory or opportunistic way. A challenge in crowd sensing as well as classical field studies is user motivation in participation and incentive mechanisms. Opportunistic crowd sensing on mobile and ubiquitous devices requires self-organising and adaptation capabilities, which cannot be satisfied by classical and centralised WEB-based services. Mobile agents (ABC) as mobile software processes can overcome limitations occurring in centralised WEB infrastructures [5]. Mobile agents provide a seamless interface between real and virtual worlds (ABMS).

II. Agent-based Crowd Sensing, Chat Bots, and Digital Twins

Classical field studies are commonly serviced by a central WEB server and WEB-based content management. These field studies address usually participative crowd sensing. Opportunistic crowd sensing can extend user classes and user numbers significantly. One promising approach supporting the human-as-sensor concept is the deployment of autonomous or semi-autonomous chat bot agents that can interact with humans on a wide range of devices, media, and social platforms. Mobile agents feature self-organising and self-adaptation.

Commonly, simulation is performed with artificial agent models derived from theoretical considerations or experimental data. Augmented virtuality enables dynamic simulations with agents representing real humans (or crowds). By using crowd sensing it is possible to create digital twins of real humans based on a parameterisable behaviour and interaction model. The parameters of artificial humans in the simulation represented by agents are collected by sensor data, i.e., surveys optionally fused with physical sensors like GPS.

It is assumed that there is a parameterisable behaviour model M of individual entities, i.e., a model of social interaction, which is used to model digital twins representing individual real humans (P : Parameter set, S : Sensor set, A : Action set):

$$M(S, P) : S \times P \rightarrow A \quad (1)$$

The individual behaviour model will result in a specific system behaviour showing emergence effects (e.g., segregation and group formation).

Mobile chat bot agents fulfil two tasks in crowd sensing: (I) Sensing of Data from the user and user devices and (II) Negotiation between the crowd sourcer and the user.

III. Extended Simulation Architecture

The software framework couples virtual and real worlds by using computational agents (chat bots) operating in virtual and real worlds and physical agents in simulation. The

chat bot agents are the interface between humans and simulation.

The entire crowd sensing and simulation architecture consists of the following components:

1. Crowd sensing software (Mobile App and WEB Browser)
2. Unified agent processing platform based on JavaScript (JavaScript Agent Machine, *JAM*)
3. Agent-based simulation with internet connectivity and two different agent types:
 - **Physical agents** representing individual artificial humans or any other physical entity
 - **Computational agents** representing mobile software, i.e., used for distributed data processing and digital communication, and implementing chat bots
4. Chat dialogues, Chat bots and Mobile agents
5. Knowledge-based Question-Answer Systems




Figure 2. Principle concept of closed-loop simulation for augmented virtuality: (Left) Simulation framework based on the JAM platform (Right) Mobile and non-mobile devices executing the JAM platform connected with the virtual simulation world (via the Internet)

The principle system architecture is shown in Fig. 2. Details can be found in [4]. *JAM* platform nodes exist in the simulator, in Internet relays, and application programs for crowd sensing operating, e.g., on mobile devices. The simulation world consists of a

set of virtual *JAM* platforms that are controlled by a physical *JAM* node. A physical *JAM* node can be connected to the Internet, virtual nodes can be connected with each other (simulating communication).

In the simulation model, there is no significant difference between physical and computational agents. The main difference is mobility (in the simulation world). Physical agents are bound to a virtual *JAM* node (*vJAM*), and the agent is mobile by its platform, whereas computational agents can migrate between platforms and between virtual and real worlds. Physical agents can access an extended programming interface (API) similar to the well-known *NetLogo* simulation model providing agent control like agent creation, movement or visual changes. An expressive *ask* operator is provided, too.

IV. Social Interaction and Segregation with the Sakoda Model

To demonstrate the augmented virtuality approach combining agent-based simulation with agent-based crowd sensing the *Sakoda* model [6] was chosen as a simple social interaction and behaviour model between groups of individual humans. It poses self-organising behaviour (emergence) and structures of social groups by segregation.

For the sake of simplicity, there is a two-dimensional grid world that consists of places at discrete locations (x,y) . An artificial agent occupies one place of the grid. Maximal one agent can occupy a place. The agents can move on the grid and can change their living position.

It is assumed that there are two groups related to the classes a and b of individuals. The social interaction is characterised by different attitudes [6] of an individual between different and among same groups given by four parameters:

$$S_{ab} = (s_{aa}, s_{ab}, s_{ba}, s_{bb}), S_{abcd} = \begin{pmatrix} s_{aa} & s_{ab} & s_{ac} & s_{ad} \\ s_{ba} & s_{bb} & s_{bc} & s_{bd} \\ s_{ca} & s_{cb} & s_{cc} & s_{cd} \\ s_{da} & s_{db} & s_{dc} & s_{dd} \end{pmatrix} \quad (2)$$

The model is not limited to two groups of individuals. The S vector can be extended to four or more groups (or generalised) by a n -dimensional matrix. Here, the S vector or matrix is the model parameter set $M(P)$ that can be used to create diverse digital twins based on surveys and crowd sensing.

The world model consists of N places x_i . Each place can be occupied by none or one agent either of group α or β , expressed by the variable $x_i = \{0, -1, 1\}$, or generalised $x_i = \{0, 1, 2, 3, 4, \dots, n\}$ with n groups. The social expectation of an individual i at place x_i is

given by:

$$f_i(x_i) = \sum_{k=1}^N J_{ik} \delta_s(x_i, x_k) \quad (3)$$

The parameter J_{ik} is a measure of the social distance (equal one for Moore neighbourhood with distance one), decreasing for longer distances. The parameter δ expresses the attitude to a neighbour place, given by (for the general case of n different groups):

$$\delta_s(x_i, x_k) = \begin{cases} s_{\alpha\beta} & , \text{ if } x_i \neq 0 \text{ and } x_k \neq 0 \text{ with } \alpha = x_i, \beta = x_k \\ 0 & , \text{ otherwise} \end{cases} \quad (4)$$

An individual agent ag_i of group α or β is able to change its position by migrating from an actual place x_i to another place x_q if this place is not occupied ($x_q=0$) and if $f_i(x_q) > f_i(x_i)$. The computation of the neighbouring social expectation f values is opportunistic, i.e., if f is computed for a neighbouring place, it is assumed that the agent occupies this neighbour place if the place is free, and the current original place x_i is omitted for this computation. Any other already occupied places are kept unchanged for the computation of a particular f value. From the set of neighbouring places and their particular social expectations for the specific agent the best place is chosen for migration (if there is a better place than the current with the above condition). In this work, spatial social distances in the range 1-30 place units are considered.

Originally, the entire world consists of individual agents interacting in the world based on one specific set of attitude parameters S . In this work, the model is generalised by assigning individual entities its own set S retrieved from real humans by crowd sensing, or at least different configurations of the S vector classifying social behaviour among the groups. Furthermore, the set of entities can be extended by humans and bots (intelligent machines) belonging to a group class, too.

V. Experiment and Evaluation

The initial simulation was carried out with a unified $S=(1,-1,-1,1)$ setting for all agents of both classes leading to classical segregation structures (strong isolated clusters), shown in Fig. 3. The social interaction distance was fixed $r=3$; In a second run, digital twins retrieved from crowd sensing surveys were added to the simulation dynamically. Some results are shown in Fig. 4. Now, the S vector and the social distance r depend on the answers given by the (real) humans, which can differ from the initial S setting and the social interaction distance r . These agents (if their S differs from the basic model) create a disturbance in the segregation patterns. Agents with $s_{\alpha\beta}=1$ and $s_{\alpha\alpha}=1$ can be integrated in both groups and are able to bind different groups close together (see the development and movement of the blue and red clusters inside the red circle in Fig. 4)




Figure 3: (a) Simulation world consisting of 200/200 artificial agents of class a/b (blue/red squares), randomly distributed (b) Simulation world after social organisation based on mobility forming strong isolated homogeneous clusters with $S=(1,-1,-1,1)$ and $r=3$ interaction radius after 200 simulation steps




Figure 4: Simulation world at different simulation times (500/1000/1500 steps) consisting of 200/200 a/b class agents (blue/red squares) all with $S=(1,-1,-1,1)$ and $r=3$ parameter settings and additionally up to 200 digital twins (triangles with colour based on individual S/r parameters)

VI. Conclusion

The MAS simulation framework, introduced in this work, is suitable to combine social and computational simulations with real-world interaction at run-time by integrating crowd sensing and by using mobile agents. A simple use-case demonstrated social interaction and social structure formation based on a parametrisable Sakoda model ex-

tended with digital twins retrieved by agent-based crowd sensing integrated in and extending agent-based simulation. The crowd sensing surveys performed by mobile agents is used to create digital twins of real humans in the simulation world (with respect to the social interaction model and mobility) based on individual surveys via a chat bot dialogue.

VII. References

1. F.-Y. Wang, *Agent-Based Control for Networked Traffic Management Systems*, Intelligent Transportation Systems, no. September/October, 2005.
2. H. Hamidi and Ali Kamankesh, *An Approach to Intelligent Traffic Management System Using a Multi-agent System*, Int. J. ITS Res. (2018), vol. 16, pp. 112-124
3. O. Baqueiro, Y. J. Wang, P. McBurney, and F. Coenen, *Integrating Data Mining and Agent Based Modeling and Simulation*, in *ICDM 2009, LNAI 5633*, 2008.
4. S. Bosse, U. Engel, *Augmented Virtual Reality: Combining Crowd Sensing and Social Data Mining with Large-Scale Simulation Using Mobile Agents for Future Smart Cities*, Proceedings, Volume 4, ECSA-5 5th International Electronic Conference on Sensors and Applications 15–30 November, 2018 DOI 10.3390/ecsa-5-05762
5. T. Leppänen, J. Á. Lacasia, Y. Tobe, K. Sezaki, and J. Riekkı, *Mobile crowd-sensing with mobile agents*, Autonomous Agents and Multi-Agent Systems, vol. 31, no. 1, pp. 1-35, 2017.
6. P. Medina, E. Goles, R. Zarama, and S. Rica, *Self-Organized Societies: On the Sakoda Model of Social Interactions*, Complexity, 2017.